

HF-TP-RW-232-IP-D2

13.56Mhz Triple Protocol RFID Reader/Writer with RS232 & TCP/IP interface

Support Triple Protocol : ISO14443A , ISO14443B & ISO15693

Features :

- Support ISO14443A , ISO14443B & ISO15693 RF interface
- ISO15693 - support anti-collision
- Operation frequency : 13.56Mhz
- Built-in transceiver antenna;
- Reading distance up to ~5-8cm (for ISO card size)
- Less than 100ms decoding time;
- Built-in bi-color LED and buzzer
- Interface : RS232 & TCP/IP (virtual Com)



Triple Protocol Support

ISO15693	ISO14443A	ISO14443B
- TI (Tag It)	- Mifare S50	- AT88RF020
- NPX (I-code SLI)	- Mifare S70	- SR176
- SRF55V02P	- Mifare ultra light	- SR1X4K
- SRF55V10P		- THR1064

Size : (100x120x30)mm

Software pack :

- Demo program - show how to read & write the data into the tag
- example source code - speed up software development time (VB.NET , C# and Delphi)
- speed up software development time
- detail DLL command set and manual
- data sheet & user manual
- TCP/IP to virtual com driver

Ordering Part No :

HF-TP-RW-232-IP-D2	13.56Mhz Triple Protocol RFID Reader/Writer with RS232 & TCP/IP interface
--------------------	---